

Thank you for purchasing a Sargent Rear Heated Seat for your Multistrada. Please take a few minutes to review the information below. This document is to be used in conjunction with the general Sargent Ducati Multistrada Seat installation instructions, and the Sargent Heated Seat Control Wiring Instructions included with the heat control unit. Please read these two general instructions first in their entirety; then apply these supplemental instructions to the heated passenger seat installation.

INSTALLATION:

1. Plan the placement and wire routing for the driver and passenger heat control units. **NOTE: BOTH front and rear Sargent Heat Controller connections will be made under the FRONT seat.**
2. Install front seat per the Sargent seat installation instructions, ensuring the rear most heat wire extends toward the rear of the bike and under the passenger seat area.
3. When installing the rear seat, plug the rear most heat wire coming from the front seat, into the plug under the rear seat. (See FIG. 1)
4. Place the wire in the **wire guide slot** located in the front of the rear pan as shown below and hold in place. (See FIG. 2)
5. Feed any excess wire under the **rear** seat pan, while maneuvering the rear seat in place per the Sargent seat installation instructions.
6. **Watch the wire as you latch the rear seat to ensure the heat wire remains in the rear pan guide slot and free from being pinched by adjacent panels and support bumpers before latching the seat. Excess wire should be directed under the rear seat.**



FIG 1.



FIG 2.